



Flexiwet™ CZ-1000

Non-fluorinated Surfactant

Overview

- Non-fluorinated surfactant mixture
- Provides anti-blocking for paints & coatings
- Surface tension reduction at low loading levels without increased foaming
- Powerful wetting and leveling performance for smoother, defect-free coatings & improved open time
- Does not impart color, or change the optical properties of a coating (beyond potential gloss or DOI - distinctness of image)
- Aqueous Surface Tension, de Nouy ring @ 25°C:

0.05% in water	30.8 dynes/cm
0.10% in water	29.2 dynes/cm
0.50% in water	22.5 dynes/cm

Applications

- Additive for paints & coatings
- Additive for adhesives
- Additive for mold release
- Additive for polishes & lacquers
- Surfactant for HI&I cleaning formulations

Technical Information

Flexiwet CZ-1000 is a non-fluorinated surfactant mixture for use in paints & coatings, adhesives, mold release, and HI&I cleaning formulations.

Surface tension reduction can be achieved at low loading levels. This product is an excellent choice for wetting difficult-to-wet substrates such as plastics, oily substrates, and waxy surfaces. The excellent wetting and leveling provides smoother, defect-free coatings. Surface diffusion properties of Flexiwet CZ-1000 deliver block resistance, mold release, and improved release properties for adhesives.

A neutralized version of this product is available as Flexiwet CZ-1040K.

Formulary

This product is self-dispersible in water, with added IPA or glycol.

The recommended use level for Flexiwet CZ-1000 is 0.1 to 1.0 wt. % (as sold) in the final formulation.

Flexiwet CZ-1000 can be incorporated during the letdown phase of production or post-added to the final formulation.

Typical Properties*

PROPERTY	VALUE
Appearance	Clear, viscous liquid
Color	Colorless to lt. amber Gardner color: 7 max
Odor	Mild
% Solids	94.0 minimum
Ionic character	Free acid (est. 580 mg. KOH/g.)
Solubility	Self-dispersible in water, with added IPA or glycol
pH (as is)	0.8 to 2.0
Density@25°C	1.13 to 1.17 g/ml
Viscosity	1000 cPs max.
Flash point	> 94°C (closed cup)
Storage	Perishable if frozen
Shelf life	24 months

*Typical Properties do not represent specification ranges.

Packaging and Handling

Flexiwet CZ-1000 is available in:
275 gallon totes (2205 lb. net wt.),
55 gallon drums (441 lb. net wt.)
5 gallon pail (40 lb. net wt.)

Refer to the Safety Data Sheet (SDS) for information on the safe use, handling, and disposal of this product.

DOT Classification: Corrosive liquid,
Hazard Class 8, UN 3265, PG I

Whether you're looking for a replacement product or an ingredient for a specific attribute, give us a call. We can provide assistance based upon your particular formulation requirements and composition; please feel free to contact us.

Flexiwet CZ-1000

Non-fluorinated Surfactant

This information relates only to the specific material referred to herein and not to its use in combination with any other material or in any process, unless explicitly stated herein. Such information is, to the best of our knowledge and belief, accurate and reliable as of the date compiled; however, no warranty, guarantee or other representation is made as to its accuracy, reliability, or completeness, or regarding any liabilities arising from others' intellectual property rights. ID# 20240412. rev 1