

Flexiwet™ CZ-1040K

Non-fluorinated Surfactant

Overview

- · Non-fluorinated surfactant mixture
- Provides anti-blocking for paints & coatings
- Surface tension reduction without increased foaming
- Powerful wetting and leveling performance for smoother, defectfree coatings & improved open time
- Does not impart color, or change the optical properties of a coating (beyond potential gloss or DOI distinctness of image)
- Aqueous Surface Tension, de Nouy ring @ 25°C:

0.05% in water 37.2 dynes/cm 0.10% in water 37.2 dynes/cm 0.5% in water 21.8 dynes/cm

Applications

- · Additive for paints & coatings
- Additive for adhesives
- · Additive for mold release
- Additive for polishes & lacquers
- Surfactant for HI&I cleaning formulations

Technical Information

Flexiwet CZ-1040K is a non-fluorinated surfactant mixture for use in paints & coatings, adhesives, mold release, and HI&I cleaning formulations.

Surface tension reduction can be achieved at low loading levels. This product is an excellent choice for wetting difficult-to-wet substrates such as plastics, oily substrates, and waxy surfaces. The excellent wetting and leveling provides smoother, defect-free coatings. Surface diffusion properties of Flexiwet CZ-1040K deliver block resistance, mold release, and improved release properties for adhesives.

Flexiwet CZ-1040K is a neutralized version of Flexiwet CZ-1000.

Formulary

This product is water soluble. The recommended use level for Flexiwet CZ-1040K is 0.2 to 2.0 wt. % (as sold) in the final formulation.

Flexiwet CZ-1040K can be incorporated during the letdown phase of production or post-added to the final formulation.

Typical Properties*

PROPERTY	VALUE
Appearance	Liquid
Color	Colorless to light amber
Odor	Mild
% Solids	40 to 45.5
Ionic character	slightly alkaline
Water Solubility	Soluble
pH (as is)	5 to 8
Density@25°C	1.1 to 1.2 g/ml
Boiling Point	> 94°C
Flash point	> 94°C (closed cup)
Storage	Perishable if frozen
Shelf life	12 months

*Typical Properties do not represent specification ranges.

Packaging and Handling

Flexiwet CZ-1040K is available in: 275 gallon totes (2500 lb. net wt.), 55 gallon drums (500 lb. net wt.), 5 gallon pail (40 lb. net wt.)

Refer to the Safety Data Sheet (SDS) for information on the safe use, handling, and disposal of this product.

DOT Classification: Not DOT regulated

Whether you're looking for a replacement product or an ingredient for a specific attribute, give us a call. We can provide assistance based upon your particular formulation requirements and composition; please feel free to contact us.

Flexiwet CZ-1040K **Non-fluorinated Surfactant**

This information relates only to the specific material referred to herein and not to its use in combination with any other material or in any process, unless explicitly stated herein. Such information is, to the best of our knowledge and belief, accurate and reliable as of the date compiled; however, no warranty, guarantee or other representation is made as to its accuracy, reliability, or completeness, or regarding any liabilities arising from others' intellectual property rights. ID# 20240109. revision 2.

